

INVESTIGATION ON THE POSSIBILITY OF USING NATURAL RUBBER SEED OIL AS BRAKE FLUID

*¹AKPAN, W.A ² IKRANG, E.G AND ³ ASANGUSUN, P.

¹ Department of Mechanical Engineering, University of Uyo, Nigeria

² Department of Agric/Food Engineering, University of Uyo, Nigeria

³ Department of Chemical/Petroleum Engineering, University of Uyo,
Nigeria

Abstract

This paper studies the possibility of using natural rubber seed oil as a brake fluid. The laboratory properties of both standard brake fluid and rubber seed oil were determined. The actual test of the braking efficiencies of the brake fluids were carried out with a Mercedes 190 model within the speed range of 20km/hr to 90km/hr at the permanent campus of University of Uyo and the braking efficiency of 93.45% for the standard brake fluid and 90.24% for the natural rubber oil seed were obtained. This result shows that natural rubber seed oil is suitable for use as a brake fluid.

Keywords: Brake fluid, natural rubber seed , brake properties, braking efficiency

INTRODUCTION

In fluids deformation takes place and the particles continuously change their positions relative to one another Bernard (2001), (Hannah et al.,1985}. It offers no lasting resistance to displacement. Deformation of the fluid takes place continuously so long as a shear force is applied .But if this force is removed the shearing movement subsides and as there are no forces tending to return the particles of fluid to their original relative positions, the fluid keeps its new shape (Bernard, 2001) .Fluids may be

divided into liquids and gases. Under ordinary conditions liquids are so difficult to compress and for most purposes may be regarded as incompressible, however gases may be much more easily compressed (Douglas et al., 1985). Fluids have unique and distinct properties that enable its application in Engineering. The brake fluid is a very important component of the braking system. It assists the braking system to bring a moving mass to rest. Most of the brake fluids that are in use are glycol-ether based though mineral oil and silicone-based fluids also exist. These brake fluid must meet the standard spelt out by various organizations. Brake fluids are classified according to their physical properties. The standards in the US come from the Department of Transportation (DOT) (1971). Thus we have DOT 3, DOT 5 and DOT 5.1. The society of Automotive Engineers SAE has similar standards of SAE J1703, J1704 and J1705 (1983). The international organization for standardization (ISO) 4925 SPECIFICATIONS exist for non-petroleum based brake fluids for hydraulic system.

The two commonly available types of brake fluids are- Glycol-ester blends. These glycol-based fluids normally have low compressibility but are hygroscopic in nature. The dry boiling point of glycol based fluid seldom exceeds 304°C . The second classification which is ester-based has higher dry and wet boiling points. It is not hygroscopic but it is more expensive than the glycol-based fluids. **These types of brake fluids are expensive and the petroleum based brake fluids have serious effect on the environment.**

There are numerous properties which a fluid must possess for it to be considered as a brake fluid. These properties are: Dry and wet equilibrium boiling point, viscosity, pH value, fluid stability. Corrosion resistant, fluidity and appearance at low temperature, water tolerance, resistant to oxidation, swell test, compressibility test, chemical stability, compatibility. The brake fluid must possess a high boiling point to avoid it vaporizing and becoming spongy. It must not boil after accepting a certain amount of moisture. The brake fluid must also possess high viscosity and should not change under a wide range of temperatures. The pH value should not be less than 7.0 or more than 11.5. Brake fluid should not be corrosive. Brake fluid must maintain low compression despite variance operating temperature. The braking efficiency is said to be 100% when the braking force is equal to the weight of the vehicle, or when deceleration is 9.81m/s^2 (Dolan, 1991). An efficiency of 100% is not desirable because of the rapid wear of the brake linings and tyres, discomfort to passengers and the risk of losing control of the vehicle. It is generally accepted that brake efficiency of 80% to 85% should be aimed at (Dolan 1991). **Little attention**

has been paid to the seeds of natural rubber tree, unknown that it contains valuable oil which has potential application in the production of soap, cosmetics, paints, glazing pottery as well as brake fluids. Large quantities of rubber seeds abound in Nigeria. About 42, 980 metric tons of the seeds could be produced annually in the country. However, the amount of the seed that could be produced in any year is influenced by factors such as powder mildews disease, abnormal leaf disease, phytophthora disease, genetics and weather. There is need to explore other viable economic use of rubber seed in the country and this calls for this research study.

The rubber seeds usually mature and dehisces from the seed pods during the short dry period between August and September in the rubber belt in Southern Nigeria. The oil content in dried Kernel varies 35 to 45% . Two products are obtainable from rubber seeds and they are the oil and the cake. The oil is semi-drying, yellowish and consist of 17 – 82% unsaturated fatty acids and 17-22% saturated fatty acids.

The main objective of this paper is to determine the possibility of using natural rubber seed oil as a brake fluid.

MODELS AND THEORIES

The braking force is derived from the applied pressure in a confined fluid and if the fluid is incompressible that pressure is transmitted equally in all directions throughout the fluid. Work is done by the applied force which pushes a friction plate onto the rotating brake drum .When rotating members of a machine are caused to stop by means of a brake, the kinetic energy is absorbed. The energy absorbed by the brake depends on the type of motion, such motion could be translational , pure rotational or both Shigley (1977) ; (Khurmi et al., 2005).

For pure translation motion, the energy absorbed is:

$$E_1 = \frac{1}{2} m(v_1^2 - v_2^2) \quad 1$$

Where E is the energy absorbed, m the mass and v_1 and v_2 are the initial and final velocities

respectively, If the moving mass is brought to rest after the braking, then v_2 is zero

Thus,

$$78 \quad E_1 = \frac{1}{2} m(v_1^2) \quad 2$$

79 In pure rotational motion the kinetic energy of the rotation is expressed as:

$$80 \quad E_2 = \frac{1}{2} m(\omega_1^2 - \omega_2^2) \quad 3$$

81 Where ω_1 and ω_2 are the initial and final angular velocities.

82 If the moving body is stopped after applying the brake, ω_2 is equal to zero.

$$83 \quad E_2 = \frac{1}{2} m(\omega_1^2) \quad 4$$

84 For both translational and rotational motion, the total kinetic energy involved is:

$$85 \quad E_T = E_1 + E_2 \quad 5$$

86 Work done by the braking force in time t seconds is :

$$87 \quad W = F_t \times \Pi d N x t \quad 6$$

88 Where F_t is the braking or frictional force, d the diameter of the brake drum, N, mean speed of the brake
89 drum and Π a constant.

90 The total energy to be absorbed by the brake must be equal to the work done by the frictional force, thus:

$$91 \quad E_T = W \quad 7$$

92 The heat developed during braking is transformed into heat and lost into the surrounding air in order to
93 avoid excessive temperature of the brake lining, wheel and tyres. The heat generated is given as :

$$94 \quad H_g = \mu R_N v = \mu \rho A v \quad 8$$

95 Where H_g is the heat generated, R_N normal force acting at the contact surface (N), ρ normal

96 pressures between the braking surfaces ($\frac{N}{m^2}$) A, the area m^2 and v the peripheral velocity m/s

97 The heat dissipated is estimated from:

$$98 \quad H_d = C(t_1 - t_2) A_t \quad 9$$

Where H_d is the heat dissipated, C is the dissipation coefficient of heat transfer ($W/m^2/^\circ C$)

t_1, t_2 are the temperature differences between the exposed radiating surface and the surrounding air and

A_t area of radiating surface (m^2).

The rise in the temperature of the brake drum is given as :

$$\Delta t = \frac{H_g}{mc} \quad 10$$

C is the specific heat capacity of the material of the brake drum ($J/Kg^\circ C$)

MATERIAL AND METHODS

Rubber seeds (*Hevea brasiliensis*) were obtained at PAMOL Nigeria Limited, a rubber plantation at Calabar Municipal Local Government Area, Cross River State, Nigeria. The seeds were dehulled, cleaned and dried under the sun for three (3) days to ensure that water moisture was removed. It was then grinded or ground into paste using a mortar and pestle in order to weaken and rupture the cell. The paste was stored in a labeled airtight container for oil extraction. All chemicals and reagents used were of analytical grade. In all cases, distilled water was used. For each specimen, oil was extracted from the paste with n-hexane solvent for three hours, using the Soxhlet apparatus. The viscosity, the dry boiling, wet boiling points, pH value, fluid stability, corrosion test of the oil were all determined and the values compared with the standard commercial DOT 3 brake fluid.

The brake fluid line was emptied and flushed before the inclusion of the natural rubber seed oil fluid in the system. The fluid line was bled to remove any entrapped air. The live test was conducted using a Mercedes 190 model car of about 3000kg. Before conducting the test the brake system and the tyres were checked to be in good conditions. A point was marked on a tarred road for an experienced driver to start to apply his brake. When the car finally comes to rest that point was also noted. The distance between when the brake was applied and when the car stops was measured. The time interval of each activity was measured. For each speed limit six values were obtained and the mean data recorded. The speed range used was between 20km/hr to 90km/hr.

RESULTS AND DISCUSSION

124 The measured physical properties of the DOT 3 standard brake fluid and natural rubber seed oil brake
 125 fluid are presented in (table 1.) The physical properties of natural rubber seed oil match closely with the
 126 DOT 3 brake fluid .The boiling point natural rubber seed oil brake fluid is within the range stipulated and is
 127 close to that of the commercial DOT 3 brake fluid used for the study. Natural rubber seed oil has a higher
 128 wet equilibrium boiling point of 172.5°C compared to 162.5°C of the DOT 3 brake fluid which shows
 129 that it less hygroscopic . The natural rubber seed oil also possesses a higher viscosity of $48.0 \times 10^{-6} \text{ m}^2/\text{s}$
 130 than the DOT 3 of $43.90 \times 10^{-6} \text{ m}^2/\text{s}$ and, this may have hindered the flow characteristics of the natural
 131 rubber seed oil and account for the reduction in braking efficiency compared to the DOT 3 brake fluid
 132 used for this study. The natural rubber seed oil is also chemically stable as shown in(table 1)

133

134 **Table 1: Physical properties of a standard brake fluid and natural rubber seed oil**

S/N	FLUID PROPERTIES	STANDARD DOT 3 BRAKE FLUID	NATURAL RUBBER SEED OIL
1.	Equilibrium reflux boiling point ERRP	245°C	235°C
2.	Wet ERBP	162.5°C	158°C
3.	pH value	9.5 at 32°C	6.5 at 32°C
4.	Dynamic viscosity	402.39×10^{-10} Ns/m^2	$455.5 \times 10^{-10} \text{ Ns}/\text{m}^2$
5.	Kinematic viscosity	$43.90 \times 10^{-6} \text{ m}^2/\text{s}$	$48.0 \times 10^{-6} \text{ m}^2/\text{s}$
6.	High temperature stability	Stable (243.75°C)	Stable (234°C)
7.	Chemical stability	Stable (181.25°C)	Stable (185°C)
8.	Fluidity and appearance (colour)	Amber	Dark brown
9.	Water tolerance	Tolerant	Tolerant
10.	Compatibility	Compatible	compatible

135

136

137

138

139 The chemical stability ensures that the fluid does not decompose at the stipulated operating temperature.

140 The Ph value of 6.5 requires chemical treatment to make the fluid more basic like the SBF which has a

141 Ph value 9.5 at the measured temperature (Table 1)

142 The performance data of the standard and the natural rubber seed oil brake fluids are presented in([table

143 2).

144

145 **Table 2: Performance Test of Standard Brake Fluid**

S/NO.	Speed (m/s)	Braking Distance (m)	Braking time(s) (SBF)	Deceleration (m/s^2) (SBF)	Braking time(s) (NRF)	Deceleration (m/s^2) (NRF)	Applied force (N) (SBF)	Applied force (N) (NRF)	Energy Absorbed (J)
1	5.56	3.50	2,4	4.42	3.01	3.82	13,260	11,460	46,370.40
2	11.11	8.00	4,01	7.71	3.48	7.71	23,130	23,130	185,148.15
3	16.67	14.00	4.25	9.92	4.13	8.66	29,760	25,980	416,833.35
4	22.22	25.50	5.00	9.87	5.12	9.83	29,610	29,490	740,593.60

146 *SBF – Standard brake fluid * NRF -Natural rubber oil brake fluid

(Table 3) shows the corrosive test results for the two brake fluids. The lack of change in mass of the specimen for closed and opened system study show that both the standard brake fluid and the natural seed oil are not corrosive.

Table 3: Corrosive effect of Standard Brake and Natural rubber seed oil Fluid on Metal Strips

S/N	Material	Original Mass (g) in SBF	Mass after 4 days in a closed system (g) in SBF	Mass after 6 days in an open system (g) in SBF	Original Mass (g) in NRF	Mass after 4 days in a closed system (g) in NRF	Mass after 6 days in an open system (g) in NRF
1	Brass	10.12	10.12	10.12	10.14	10.14	10.14
2	Copper	10.18	10.18	10.18	10.18	10.18	10.18
3	Aluminum	15.47	15.47	15.47	16.26	16.26	16.26
4	Steel	25.38	25.38	25.38	46.78	46.78	46.78
5	Cast iron	50.05	50.05	54.05	78.87	78.87	78.87

(Table 4) shows the braking efficiency of the two fluids .The natural rubber seed oil brake fluid gives an average braking efficiency of 90.24% which is more than the minimum required-80% (Doland, 1991) and close to 93.45% obtained from DOT 3 used in this case study The braking efficiency of the natural rubber seed oil is higher than that of soya bean oil -89%, cotton seed oil- 90.4% and formulated water based brake fluid of 88% (Akpan et al; 2012; Akpan; et al ; 2012 and Akpan: et al ; 2012)

Table 4: Braking efficiency of the two brake fluids

Speed (m/s)	Deceleration (m/s ²)	Deceleration (m/s ²)	Braking efficiency Of a standard DOT 3 brake fluid %	Braking efficiency Of natural rubber seed oil brake fluid %
5.56	4.42	3.82	70.20	60.9
11.11	7.71	7.71	78.9	78.9
16.67	9.92	8.66	99.8	90.8
22.22	9.87	9.83	99.2	99.8
Average braking efficiency			93.45	90.24

CONCLUSION

From the laboratory and live test results presented, natural rubber seed oil is effective for use as a brake fluid. The natural rubber seed oil possesses good hydraulic properties which can be used in other areas of hydraulics and fluid machinery. The natural seed oil brake fluid is not corrosive and other desired fluid properties can be enhanced by the addition of additives.

REFERENCES

- Massey, B Mechanics of fluids, Nelson Thomes Ltd, United Kingdom 2001
- Hannah, J and Hillier, M.J Applied Mechanics Pitman;1985
- Douglas, J.F and Gasiorek, J.M Fluid Mechanics, Barth Press, United Kingdom;1985
- U.S. Department of Transportation Federal Motor Carrier Safety Administration Part 571116
- Standard No. 116, Motor vehicle brake fluids 1971 .Accessed 2 January 2013
- Available:<http://www.fmcsa.dot.gov/rules>

171 regulations/administration/fmcsruletext.aspx?chunkkey=090163348008f29a

172 SAE Motor Vehicle Brake Fluid, SAE standard J1703 NOV83;1983

173

174 Dolan, J.A Motor Vehicle Technology and practical work Heinemann Educational books

175 Plc Nigeria ;1991

176 Khurmi, R.S and Gupta, J. K A Textbook of Machine Design, S Chand and company

177 Ltd , New Delhi;2006

178

179 Shigley, E. S. Mechanical Engineering Design. Mcgraw-hill book company;1977

180 Akpan, W.A.; Ufot E.and Ikrang, E.G, . Investigation into the use of soya bean oil as brake fluid

181 International Journal of Engineering 2012 Vol.6 No. 1 International center for advance studies.

182 West Bengal India

183

184 Akpan, W.A.;E, Ufot E.and Ikrang, E.G.. Hydrualic Investigation into the use of cotton seed oil

185 as brake fluid International Journal of Engineering 2012 Vol.6 No. 2 International center for

186 advance studies. West Bengal India

187

188 Akpan, W.A.;. Ikrang, E.G: E. Markson. P. Asangusung . Investigation into the use of water

189 based brake fluid for light loads.2012 International Journal of Technological Development,

190 Faculty of Engineering. University of Ilorin, Ilorin, Nigeria