

2-tuple prioritized aggregation operators and their application to multiple attribute group decision making

Zhiming Zhang*

¹College of Mathematics and Computer Science, Hebei University, Baoding 071002, Hebei Province, PR China

ABSTRACT

Aims: The aim of this paper is to present some 2-tuple prioritized aggregation operators for handling the multiple attribute group decision making problems where there exists a prioritization relationship over the attributes and decision makers.

Study design: Motivated by the idea of the prioritized aggregation (PA) operators, we first develop two 2-tuple prioritized aggregation operators called the 2-tuple prioritized weighted average (2TPWA) operator and the 2-tuple prioritized weighted geometric (2TPWG) operator.

Place and Duration of Study: We examine their desirable properties.

Methodology: The significant feature of these operators is that they not only deal with the linguistic and interval linguistic information but also take the prioritization relationship among the arguments into account.

Results: Then, based on the proposed operators, we propose an approach to multiple attribute group decision making under linguistic environment in which the attributes and decision makers are in different priority level.

Conclusion: Finally, an illustrative example is employed to show the reasonableness and effectiveness of the proposed approach.

Keywords: Multiple attribute group decision making; 2-tuple linguistic information; 2-tuple prioritized weighted average (2TPWA) operator; 2-tuple prioritized weighted geometric (2TPWG) operator.

1. INTRODUCTION

Multiple attribute group decision making (MAGDM) consists of finding the most desirable alternative(s) from a given alternative set according to the preferences provided by a group of experts [16,44-49]. For some MAGDM problems, the decision information about alternatives is usually uncertain or fuzzy due to the increasing complexity of the socio-economic environment and the vagueness of inherent subjective nature of human thinking [2,9,19]; thus, the decision information cannot be precisely assessed in a quantitative form. However, it may be appropriate and sufficient to assess the information in a qualitative form rather than a quantitative form. For example, when evaluating a house's cost, linguistic terms such as "high", "medium", and "low" are usually used, and when evaluating a house's design, linguistic terms like "good", "medium", and "bad" can be frequently used. Up to now, some methods have been developed for coping with linguistic information. These methods can be summarized as follows [22]: (1) The approximative computational model based on the Extension Principle [5]. This model transforms linguistic assessment information into fuzzy numbers and uses fuzzy arithmetic to make computations over these

* Tel.: +86 312 5079660; fax: +86 312 5079660.
E-mail address: zhimingzhang@ymail.com.

fuzzy numbers. The use of fuzzy arithmetic increases the vagueness. The results obtained by the fuzzy arithmetic are fuzzy numbers that usually do not match any linguistic term in the initial term set. (2) The ordinal linguistic computational model [7]. This model is also called symbolic model which makes direct computations on labels using the ordinal structure of the linguistic term sets. But symbolic method easily results in a loss of information caused by the use of the round operator. (3) The 2-tuple linguistic computational model [12,13,14,15]. This model uses the 2-tuple linguistic representation and computational model to make linguistic computations. (4) The model, which computes with words directly [24,26,27,28,29,30,31,32,33].

The 2-tuple fuzzy linguistic representation model represents the linguistic information by means of a pair of values called 2-tuple, composed by a linguistic term and a number. Meanwhile, the model also gives a computational technique to deal with the 2-tuples without loss of information. Since its introduction, the 2-tuple fuzzy linguistic representation model has received more and more attention. In a MAGDM problem involving the 2-tuple fuzzy linguistic representation model, in order to aggregate the individual linguistic preference information into the overall linguistic preference information, 2-tuple aggregation operators are most widely used. In the past few decades, many scholars have developed a variety of 2-tuple aggregation operators, such as 2-tuple arithmetic mean operator [12,14], 2-tuple weighted averaging operator [12], 2-tuple OWA operator [12], 2-tuple weighted geometric averaging (TWGA) operator [34], 2-tuple ordered weighted geometric averaging (TOWGA) operator [34], 2-tuple hybrid geometric averaging (THGA) operator [34], 2-tuple arithmetic average (TAA) operator [12], 2-tuple weighted average (TWA) operator [12], 2-tuple ordered weighted average (TOWA) operator [12], extended 2-tuple weighted average (ET-WA) operator [12], 2-tuple ordered weighted geometric (TOWG) operator [18], extended 2-tuple weighted geometric (ET-WG) operator [21], extended 2-tuple ordered weighted geometric (ET-OWG) operator [21], generalized 2-tuple weighted average (G-2TWA) operator [22], generalized 2-tuple ordered weighted average (G-2TOWA) operator [22], induced generalized 2-tuple ordered weighted average (IG-2TOWA) operator [22], 2-tuple linguistic power average (2TLPA) operator [36], 2-tuple linguistic weighted power average (2TLWPA) operator [36], and 2-tuple linguistic power ordered weighted average (2TLPOWA) operator [36].

The above MAGDMs are under the assumption that the attribute and the decision makers are at the same priority level respectively. In this situation, we have the ability to trade off between attributes. For instance, if C_i and C_j are two attributes with the weights w_i and w_j respectively, then we can compensate for a decrease of q in satisfaction to attribute C_i by

gain $\frac{w_j}{w_i}q$ in satisfaction to attribute C_j . However, in some MAGDM problems, we do not

want to allow this kind of compensation between attributes. For example, consider the situation in which we are buying a car based on the safety and cost of cars. We may not allow a benefit with respect to cost to compensate for a loss in safety. In this case we have a kind of prioritization of the attributes, i.e., safety has a higher priority than cost. Additionally, decision making in a company, general manager has a higher priority than vice manager. Yager [38] first investigated criteria aggregation problems where there is a prioritization relationship over the criteria. Then, Yager [39] and Yager et al. [40] gave much deeper insights into this issue. Motivated by the ideas of Yager [38,39] and Yager et al. [40], Wei [23] generalized prioritized aggregation operators to hesitant fuzzy environment, proposed some hesitant fuzzy prioritized aggregation operators, and applied these operators to develop some models for hesitant fuzzy multiple attribute decision making problems in which the attributes are in different priority level. Yu and Xu [42] investigated the prioritization relationship of attributes in multi-attribute decision making with intuitionistic fuzzy information and developed some prioritized intuitionistic fuzzy aggregation operators by extending the prioritized aggregation operators. Yu et al. [41] proposed some interval-valued intuitionistic

87 fuzzy prioritized aggregation operators and investigated the application of these operators in
 88 the group decision making under interval-valued intuitionistic fuzzy environment in which the
 89 attributes and experts are in different priority level. However, the existing 2-tuple aggregation
 90 operators are difficult to deal with the MAGDM where the attributes and the decision makers
 91 are in different priority level respectively. Moreover, we are conscious that there has been
 92 rather little work completed for using prioritized aggregation operators to solve the MAGDM
 93 with linguistic preference information. Thus, it is necessary to extend prioritized aggregation
 94 operators to the linguistic environment. To do it, in the current paper, we develop some 2-
 95 tuple prioritized aggregation operators. The prominent characteristic of these proposed
 96 operators is that they take prioritization among the attributes and the decision makers into
 97 account. Then, we utilize these operators to develop some approaches to the MAGDM
 98 where the attributes and the decision makers are in different priority level. Finally, some
 99 numerical examples are given to verify the practicality and effectiveness of the proposed
 100 operators and approaches.

101 This paper is organized as follows. Section 2 introduces some basic concepts of the 2-tuple
 102 fuzzy linguistic approach and the prioritized average operator. In Section 3, we propose the
 103 2-tuple prioritized weighted average (2TPWA) operator and the 2-tuple prioritized weighted
 104 geometric (2TPWG) operator to aggregate the linguistic information. Furthermore, we
 105 develop a method for MAGDM based on the proposed operators under the linguistic
 106 environment. In Section 4, an example concerning talent introduction is provided to
 107 demonstrate the practicality and effectiveness of the developed approach. The final section
 108 offers some concluding remarks.

109

110 2. PRELIMINARIES

111

112 In this section, we will introduce the basic notions of the 2-tuple fuzzy linguistic approach and
 113 the prioritized average operator.

114 2.1. The 2-tuple fuzzy linguistic representation model

115 Let $S = \{s_i | i = 0, 1, 2, \dots, g\}$ be a finite and totally ordered discrete linguistic term set with odd
 116 cardinality, where s_i represents a possible value for a linguistic variable, and it should satisfy
 117 the following characteristics [4, 12, 13, 14, 17, 43].

- 118 (1) The set is ordered: $s_i \geq s_j$ if $i \geq j$;
- 119 (2) There is the negation operator: $neg(s_i) = s_j$ such that $j = g - i$;
- 120 (3) Max operator: $\max(s_i, s_j) = s_i$ if $s_i \geq s_j$;
- 121 (4) Min operator: $\min(s_i, s_j) = s_i$ if $s_i \leq s_j$.

122 For example, a set of seven terms S could be given as follows [1, 3, 6, 8, 10, 11]:

123 $S = \{s_0 = \text{nothing}, s_1 = \text{very low}, s_2 = \text{low}, s_3 = \text{medium}, s_4 = \text{high}, s_5 = \text{very high}, s_6 = \text{perfect}\}.$

124 To preserve all the given information, Xu [26] extended the discrete linguistic term set S to a
 125 continuous linguistic term set $\bar{S} = \{s_\alpha | s_0 \leq s_\alpha \leq s_g, \alpha \in [0, g]\}$. If $s_\alpha \in S$, then s_α is called an
 126 original linguistic term; otherwise, s_α is called a virtual linguistic term. In general, the
 127 decision maker uses the original linguistic terms to evaluate alternatives, and the virtual
 128 linguistic terms can only appear in operation.

129 Based on the concept of symbolic translation, Herrera and Martinez [12, 13] introduced a 2-
 130 tuple fuzzy linguistic representation model for dealing with linguistic information. This model
 131 represents the linguistic assessment information by means of a 2-tuple (s_i, α) , where $s_i \in S$
 132 represents a linguistic label from the predefined linguistic term set S and $\alpha \in [-0.5, 0.5]$ is
 133 the value of symbolic translation.

Definition 2.1 [12,13]. Let β be the result of an aggregation of the indexes of a set of labels assessed in a linguistic term set S , i.e., the result of a symbolic aggregation operation. $\beta \in [0, g]$, being $g+1$ the cardinality of S . Let $i = \text{round}(\beta)$ and $\alpha = \beta - i$ be two values such that $i \in [0, g]$ and $\alpha \in [-0.5, 0.5)$ then α is called a symbolic translation, where $\text{round}(\cdot)$ is the usual round operation.

Definition 2.2 [12,13]. Let $S = \{s_i | i = 0, 1, 2, \dots, g\}$ be a linguistic term set and $\beta \in [0, g]$ a value representing the result of a symbolic aggregation operation, then the 2-tuple that expresses the equivalent information to β is obtained with the following function:

$$\Delta : [0, g] \rightarrow S \times [-0.5, 0.5)$$

(1)

$$\Delta(\beta) = (s_i, \alpha) \quad , \quad \text{with} \quad \begin{cases} s_i, & i = \text{round}(\beta) \\ \alpha = \beta - i, & \alpha \in [-0.5, 0.5) \end{cases}$$

(2)

where s_i has the closest index label to β and α is the value of the symbolic translation.

Theorem 2.1 [12,13]. Let $S = \{s_i | i = 0, 1, 2, \dots, g\}$ be a linguistic term set and (s_i, α) be a 2-tuple. There is always a Δ^{-1} function such that from a 2-tuple it returns its equivalent numerical value $\beta \in [0, g] \subset R$, where

$$\Delta^{-1} : S \times [-0.5, 0.5) \rightarrow [0, g]$$

(3)

$$\Delta^{-1}(s_i, \alpha) = i + \alpha = \beta$$

(4)

It is obvious that the conversion of a linguistic term into a linguistic 2-tuple consist of adding a value zero as symbolic translation

$$s_i \in S \Rightarrow (s_i, 0).$$

Definition 2.3 [12,13]. The comparison of linguistic information represented by 2-tuples is carried out according to an ordinary lexicographic order. Let (s_k, α_k) and (s_l, α_l) be two 2-tuples, with each one representing a counting of information as follows.

(1) If $k < l$ then (s_k, α_k) is smaller than (s_l, α_l) .

(2) If $k = l$ then

• if $\alpha_k = \alpha_l$ then (s_k, α_k) , (s_l, α_l) represents the same information;

• if $\alpha_k < \alpha_l$ then (s_k, α_k) is smaller than (s_l, α_l) ;

• if $\alpha_k > \alpha_l$ then (s_k, α_k) is bigger than (s_l, α_l) .

2.2. Prioritized average (PA) operators

The prioritized average (PA) operator was originally introduced by Yager [37,38], which was defined as follows:

Definition 2.4 [38]. Let $C = \{C_1, C_2, \dots, C_n\}$ be a collection of criteria and that there is a prioritization between the criteria expressed by the linear ordering $C_1 \succ C_2 \succ C_3 \dots \succ C_n$, indicate criteria C_j has a higher priority than C_k if $j < k$. The value $C_j(x)$ is the performance of any alternative x under criteria C_j , and satisfies $C_j(x) \in [0, 1]$. If

$$PA(C_j(x)) = \sum_{j=1}^n w_j C_j(x)$$

(5)

where $w_j = \frac{T_j}{\sum_{j=1}^n T_j}$, $T_j = \prod_{k=1}^{j-1} C_k(x)$ ($j=2, \dots, n$), $T_1=1$. Then PA is called the prioritized

average (PA) operator.

176

177 3. 2-TUPLE PRIORITIZED AGGREGATION OPERATORS

178

The prioritized average operators, however, have only been used in situations where the input arguments are the exact values [37,38]. In the following, we extend the PA operator to linguistic environment and develop two 2-tuple prioritized aggregation operators, which can accommodate the situations where the input arguments are linguistic assessment information.

184 3.1. 2-tuple prioritized weighted average (2TPWA) operators

Definition 3.1. Let $\{(r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)\}$ ($r_j \in S, \alpha_j \in [-0.5, 0.5], j=1, 2, \dots, n$) be a set of 2-tuples, if

$$2TPWA((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) = \Delta \left(\frac{T_1}{\sum_{j=1}^n T_j} \Delta^{-1}(r_1, \alpha_1) + \frac{T_2}{\sum_{j=1}^n T_j} \Delta^{-1}(r_2, \alpha_2) + \dots + \frac{T_n}{\sum_{j=1}^n T_j} \Delta^{-1}(r_n, \alpha_n) \right),$$

(6)

where $T_1=1$ and $T_j = \prod_{k=1}^{j-1} \left(\frac{\Delta^{-1}(r_k, \alpha_k)}{g+1} \right)$ ($j=2, \dots, n$), then 2TPWA is called a 2-tuple prioritized weighted average (2TPWA) operator.

Theorem 3.1 (Boundedness). Let $\{(r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)\}$ be a set of 2-tuples, then

$$\min_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \leq 2TPWA((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) \leq \max_{1 \leq i \leq n} \{(r_i, \alpha_i)\}.$$

(7)

Proof. Because $\min_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \leq (r_i, \alpha_i) \leq \max_{1 \leq i \leq n} \{(r_i, \alpha_i)\}$, we have

$$\begin{aligned} & \Delta \left(\frac{T_1}{\sum_{j=1}^n T_j} \Delta^{-1} \left(\min_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \right) + \frac{T_2}{\sum_{j=1}^n T_j} \Delta^{-1} \left(\min_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \right) + \dots + \frac{T_n}{\sum_{j=1}^n T_j} \Delta^{-1} \left(\min_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \right) \right) \\ & \leq \Delta \left(\frac{T_1}{\sum_{j=1}^n T_j} \Delta^{-1}(r_1, \alpha_1) + \frac{T_2}{\sum_{j=1}^n T_j} \Delta^{-1}(r_2, \alpha_2) + \dots + \frac{T_n}{\sum_{j=1}^n T_j} \Delta^{-1}(r_n, \alpha_n) \right) \\ & \leq \Delta \left(\frac{T_1}{\sum_{j=1}^n T_j} \Delta^{-1} \left(\max_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \right) + \frac{T_2}{\sum_{j=1}^n T_j} \Delta^{-1} \left(\max_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \right) + \dots + \frac{T_n}{\sum_{j=1}^n T_j} \Delta^{-1} \left(\max_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \right) \right). \end{aligned}$$

196 That is, $\min_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \leq 2\text{TPWA}((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) \leq \max_{1 \leq i \leq n} \{(r_i, \alpha_i)\}$. $\square$

197 **Theorem 3.2** (Idempotency). Let $\{(r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)\}$ be a set of 2-tuples. If all
 198 (r_j, α_j) ($j = 1, 2, \dots, n$) are equal, i.e., $(r_j, \alpha_j) = (r, \alpha)$, for all j , then

199 $2\text{TPWA}((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) = (r, \alpha)$

200 (8)

201 **Proof.** If $(r_j, \alpha_j) = (r, \alpha)$, for all j , then we have

$$\begin{aligned}
 2\text{TPWA}((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) &= \Delta \left(\frac{T_1}{\sum_{j=1}^n T_j} \Delta^{-1}(r_1, \alpha_1) + \frac{T_2}{\sum_{j=1}^n T_j} \Delta^{-1}(r_2, \alpha_2) + \dots + \frac{T_n}{\sum_{j=1}^n T_j} \Delta^{-1}(r_n, \alpha_n) \right) \\
 &= \Delta \left(\frac{T_1}{\sum_{j=1}^n T_j} \Delta^{-1}(r, \alpha) + \frac{T_2}{\sum_{j=1}^n T_j} \Delta^{-1}(r, \alpha) + \dots + \frac{T_n}{\sum_{j=1}^n T_j} \Delta^{-1}(r, \alpha) \right) \\
 &= \Delta \left(\Delta^{-1}(r, \alpha) \left(\frac{T_1}{\sum_{j=1}^n T_j} + \frac{T_2}{\sum_{j=1}^n T_j} + \dots + \frac{T_n}{\sum_{j=1}^n T_j} \right) \right) \\
 &= \Delta(\Delta^{-1}(r, \alpha)) \\
 &= (r, \alpha).
 \end{aligned}$$

202

203 The proof is completed.

204 **Theorem 3.3** (Monotonicity). Let $\{(r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)\}$ and $\{(r'_1, \alpha'_1), (r'_2, \alpha'_2), \dots, (r'_n, \alpha'_n)\}$
 205 be two set of 2-tuples, if $(r_j, \alpha_j) \leq (r'_j, \alpha'_j)$, for all j , then

206 $2\text{TPWA}((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) \leq 2\text{TPWA}((r'_1, \alpha'_1), (r'_2, \alpha'_2), \dots, (r'_n, \alpha'_n))$

207 (9)

208 **Proof.** This proof is analogous to the proof for monotonicity of the prioritized average
 209 operator in Ref. [38]. $\square$

210 3.2. 2-tuple prioritized weighted geometric (2TPWG) operators

211 Based on the 2TPWA operator and the geometric mean, here we define a 2-tuple prioritized
 212 weighted geometric (2TPWG) operators.

213 **Definition 3.2.** Let $\{(r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)\}$ ($r_j \in S, \alpha_j \in [-0.5, 0.5], j = 1, 2, \dots, n$) be a set of
 214 2-tuples, if

$$\begin{aligned}
 2\text{TPWG}((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) \\
 = \Delta \left((\Delta^{-1}(r_1, \alpha_1))^{T_1 / \sum_{j=1}^n T_j} \cdot (\Delta^{-1}(r_2, \alpha_2))^{T_2 / \sum_{j=1}^n T_j} \cdot \dots \cdot (\Delta^{-1}(r_n, \alpha_n))^{T_n / \sum_{j=1}^n T_j} \right)
 \end{aligned}$$

215

216 (10)

217 where $T_1 = 1$ and $T_j = \prod_{k=1}^{j-1} \left(\frac{\Delta^{-1}(r_k, \alpha_k)}{g+1} \right)$ ($j = 2, \dots, n$), then 2TPWG is called a 2-tuple
 218 prioritized weighted geometric (2TPWG) operator.

219 Similar to Theorems 3.1-3.3, we have the following theorems.

220 **Theorem 3.4** (Boundedness). Let $\{(r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)\}$ be a set of 2-tuples, then

$$\min_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \leq 2TPWG((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) \leq \max_{1 \leq i \leq n} \{(r_i, \alpha_i)\} \quad (11)$$

Theorem 3.5 (Idempotency). Let $\{(r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)\}$ be a set of 2-tuples. If all (r_j, α_j) ($j = 1, 2, \dots, n$) are equal, i.e., $(r_j, \alpha_j) = (r, \alpha)$, for all j , then

$$2TPWG((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) = (r, \alpha) \quad (12)$$

Theorem 3.6 (Monotonicity). Let $\{(r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)\}$ and $\{(r'_1, \alpha'_1), (r'_2, \alpha'_2), \dots, (r'_n, \alpha'_n)\}$ be two set of 2-tuples, if $(r_j, \alpha_j) \leq (r'_j, \alpha'_j)$, for all j , then

$$2TPWG((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) \leq 2TPWG((r'_1, \alpha'_1), (r'_2, \alpha'_2), \dots, (r'_n, \alpha'_n)) \quad (13)$$

Lemma 3.1 [20,25]. Let $x_i > 0$, $\lambda_i > 0$, $i = 1, 2, \dots, n$, and $\sum_{i=1}^n \lambda_i = 1$, then

$$\prod_{i=1}^n (x_i)^{\lambda_i} \leq \sum_{i=1}^n \lambda_i x_i$$

with equality if and only if $x_1 = x_2 = \dots = x_n$.

Theorem 3.7. Let $\{(r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)\}$ be a set of 2-tuples, then we have

$$2TPWG((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) \leq 2TPWA((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)).$$

Proof. Because $\sum_{j=1}^n \left(\frac{T_j}{\sum_{j=1}^n T_j} \right) = \frac{\sum_{j=1}^n T_j}{\sum_{j=1}^n T_j} = 1$, by Definition 3.1, Definition 3.2, and Lemma 3.1,

we have

$$\begin{aligned} 2TPWG((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)) &= \Delta \left((\Delta^{-1}(r_1, \alpha_1))^{T_1 / \sum_{j=1}^n T_j}, (\Delta^{-1}(r_2, \alpha_2))^{T_2 / \sum_{j=1}^n T_j}, \dots, (\Delta^{-1}(r_n, \alpha_n))^{T_n / \sum_{j=1}^n T_j} \right) \\ &\leq \Delta \left(\frac{T_1}{\sum_{j=1}^n T_j} \Delta^{-1}(r_1, \alpha_1) + \frac{T_2}{\sum_{j=1}^n T_j} \Delta^{-1}(r_2, \alpha_2) + \dots + \frac{T_n}{\sum_{j=1}^n T_j} \Delta^{-1}(r_n, \alpha_n) \right) \\ &= 2TPWA((r_1, \alpha_1), (r_2, \alpha_2), \dots, (r_n, \alpha_n)). \end{aligned}$$

The proof is completed.

Theorem 3.7 shows that the values obtained by the 2TPWG operator are not bigger than the ones obtained by the 2TPWA operator.

3.3. An approach to multiple attribute group decision making with 2-tuple prioritized aggregation operators

In this subsection, we develop an approach to a multiple attribute group decision making problem, where the attribute values are represented by linguistic variables and there exists the prioritization relationships over the attributes and decision makers.

A group decision making problem with linguistic preference information in which the attributes and decision makers are in different priority level can be described as follows: Let

$X = \{x_1, x_2, \dots, x_m\}$ be the set of alternatives. Let $C = \{c_1, c_2, \dots, c_n\}$ be a collection of attributes

and that there is a prioritization between the attributes expressed by the linear ordering $c_1 \succ c_2 \succ c_3 \succ \dots \succ c_n$, indicate attribute c_j has a higher priority than c_k if $j < k$. Let

$D = \{d_1, d_2, \dots, d_l\}$ is the set of decision makers and that there is a prioritization between the

253 decision makers expressed by the linear ordering $d_1 \succ d_2 \succ d_3 \succ \dots \succ d_l$, indicate decision
 254 maker d_p has a higher priority than d_q if $p < q$. For each alternative $x_i \in X$, the decision
 255 maker $d_k \in D$ provided his/her preference value $r_{ij}^{(k)}$ with respect to the attribute $c_j \in C$,
 256 where $r_{ij}^{(k)} \in S$ takes the form of linguistic variables, then, all the preference values of the
 257 alternatives with respect to the attributes consist the linguistic decision matrix $R^{(k)} = (r_{ij}^{(k)})_{m \times n}$
 258 $(k = 1, 2, \dots, l)$.

259 To get the best alternative(s), we next present a method based on 2-tuple prioritized
 260 aggregation operators for multiple attribute group decision making with linguistic preference
 261 information. The proposed method is depicted as follows:

262 **Step 1.** Transform the linguistic decision matrix $R^{(k)} = (r_{ij}^{(k)})_{m \times n}$ $(k = 1, 2, \dots, l)$ into 2-tuple
 263 linguistic decision matrix $\bar{R}^{(k)} = ((r_{ij}^{(k)}, 0))_{m \times n}$ $(k = 1, 2, \dots, l)$.

264 **Step 2.** Calculate the matrices $T^{(p)} = (T_{ij}^{(p)})_{m \times n}$, $(p = 1, 2, \dots, l)$ based on the following
 265 equations:

$$266 \quad T_{ij}^{(p)} = \prod_{k=1}^{p-1} \left(\frac{\Delta^{-1}(r_{ij}^{(k)}, 0)}{g} \right) \quad , \quad p = 2, \dots, l \quad , \quad i = 1, 2, \dots, m, \quad j = 1, 2, \dots, n \quad ,$$

267 (14)

$$268 \quad T_{ij}^{(1)} = 1 \quad , \quad i = 1, 2, \dots, m, \quad j = 1, 2, \dots, n \quad .$$

269 (15)

270 **Step 3.** Utilize the 2TPWA operator:

$$271 \quad 2TPWA((r_{ij}^{(1)}, 0), (r_{ij}^{(2)}, 0), \dots, (r_{ij}^{(l)}, 0)) = \Delta \left(\frac{T_{ij}^{(1)}}{\sum_{p=1}^l T_{ij}^{(p)}} \Delta^{-1}(r_{ij}^{(1)}, 0) + \frac{T_{ij}^{(2)}}{\sum_{p=1}^l T_{ij}^{(p)}} \Delta^{-1}(r_{ij}^{(2)}, 0) + \dots + \frac{T_{ij}^{(l)}}{\sum_{p=1}^l T_{ij}^{(p)}} \Delta^{-1}(r_{ij}^{(l)}, 0) \right)$$

272 (16)

273 or the 2TPWG operator:

$$274 \quad 2TPWG((r_{ij}^{(1)}, 0), (r_{ij}^{(2)}, 0), \dots, (r_{ij}^{(l)}, 0)) = \Delta \left(\left(\Delta^{-1}(r_{ij}^{(1)}, 0) \right)^{T_{ij}^{(1)} / \sum_{p=1}^l T_{ij}^{(p)}} \cdot \left(\Delta^{-1}(r_{ij}^{(2)}, 0) \right)^{T_{ij}^{(2)} / \sum_{p=1}^l T_{ij}^{(p)}} \cdot \dots \cdot \left(\Delta^{-1}(r_{ij}^{(l)}, 0) \right)^{T_{ij}^{(l)} / \sum_{p=1}^l T_{ij}^{(p)}} \right)$$

275 (17)

276 to aggregate all the individual 2-tuple linguistic decision matrices $\bar{R}^{(k)} = ((r_{ij}^{(k)}, 0))_{m \times n}$

277 $(k = 1, 2, \dots, l)$ into the collective 2-tuple linguistic decision matrix $\bar{R} = (\bar{r}_{ij})_{m \times n} = ((r_{ij}, \alpha_{ij}))_{m \times n}$.

278 **Step 4.** Calculate the matrix $T = (T_{ij})_{m \times n}$ based on following equations:

$$279 \quad T_{ij} = \prod_{k=1}^{j-1} \left(\frac{\Delta^{-1}(r_{ik}, \alpha_{ik})}{g} \right) \quad (i = 1, 2, \dots, m, \quad j = 2, \dots, n) \quad ,$$

280 (18)

$$281 \quad T_{i1} = 1 \quad (i = 1, 2, \dots, m) \quad .$$

282 (19)

283 **Step 5.** Utilize the 2TPWA operator:

$$\bar{r}_i = (r_i, \alpha_i) = 2\text{TPWA}((r_{i1}, \alpha_{i1}), (r_{i2}, \alpha_{i2}), \dots, (r_{in}, \alpha_{in}))$$

$$= \Delta \left(\frac{T_{i1}}{\sum_{j=1}^n T_{ij}} \Delta^{-1}(r_{i1}, \alpha_{i1}) + \frac{T_{i2}}{\sum_{j=1}^n T_{ij}} \Delta^{-1}(r_{i2}, \alpha_{i2}) + \dots + \frac{T_{in}}{\sum_{j=1}^n T_{ij}} \Delta^{-1}(r_{in}, \alpha_{in}) \right)$$

285 (20)

286 or the 2TPWG operator:

$$\begin{aligned} \bar{r}_i &= (r_i, \alpha_i) = 2\text{TPWG}((r_{i1}, \alpha_{i1}), (r_{i2}, \alpha_{i2}), \dots, (r_{in}, \alpha_{in})) \\ &= \Delta \left(\left(\Delta^{-1}(r_{i1}, \alpha_{i1}) \right)^{T_{i1} / \sum_{j=1}^n T_{ij}} \cdot \left(\Delta^{-1}(r_{i2}, \alpha_{i2}) \right)^{T_{i2} / \sum_{j=1}^n T_{ij}} \cdot \dots \cdot \left(\Delta^{-1}(r_{in}, \alpha_{in}) \right)^{T_{in} / \sum_{j=1}^n T_{ij}} \right) \end{aligned}$$

288 (21)

289 to derive the collective overall preference value $\bar{r}_i = (r_i, \alpha_i)$ of the alternative x_i .

290 **Step 6.** Rank the collective overall preference values $\bar{r}_i = (r_i, \alpha_i)$ ($i = 1, 2, \dots, m$) in descending
 291 order. Rank all the alternatives x_i ($i = 1, 2, \dots, m$) and select the best one(s) in accordance
 292 with the collective overall preference values $\bar{r}_i = (r_i, \alpha_i)$ ($i = 1, 2, \dots, m$).

293 **Step 7.** End.

294

295 4. AN ILLUSTRATIVE EXAMPLE

296

297 In this section, let us consider a numerical example adapted from Herrera et al. [15], and
 298 Herrera and Herrera-Viedma [13].

299 **Example 4.1.** Suppose that an investment company wants to invest a sum of money in the
 300 best option. There is a panel with four possible alternatives in which to invest the money: (1)
 301 x_1 is a car industry; (2) x_2 is a food company; (3) x_3 is a computer company; and (4) x_4 is
 302 an arms industry. The investment company must make a decision according to the following
 303 four attributes: (1) c_1 is the risk analysis; (2) c_2 is the growth analysis; (3) c_3 is the social-
 304 political impact analysis; and (4) c_4 is the environmental impact analysis. The four possible
 305 alternatives x_i ($i = 1, 2, 3, 4$) are to be evaluated using the linguistic term set

$$S = \left\{ \begin{array}{l} s_0 = \text{extremely poor}, s_1 = \text{very poor}, s_2 = \text{poor}, s_3 = \text{slightly poor}, s_4 = \text{fair}, \\ s_5 = \text{slightly good}, s_6 = \text{good}, s_7 = \text{very good}, s_8 = \text{extremely good} \end{array} \right\}$$

307 by three decision makers d_k ($k = 1, 2, 3$) under the above four attributes, and construct,

308 respectively, the decision matrices $R^{(k)} = (r_{ij}^{(k)})_{4 \times 4}$ ($k = 1, 2, 3$) as shown in Tables 1-3. The

309 decision maker d_1 has the absolute priority for decision making, the decision maker d_2
 310 comes next. That is, there is a prioritization between three decision makers expressed by the
 311 linear ordering $d_1 \succ d_2 \succ d_3$. In three decision makers' opinion, there exists the prioritization
 312 relationship among these attributes, for example, the risk analysis of the candidate is the
 313 most important, but the environmental impact analysis of the candidate is not so important
 314 comparing with other attributes. Therefore, the prioritization relationship can be denoted by:
 315 $c_1 \succ c_2 \succ c_3 \succ c_4$.

316 **Table 1.** Decision matrix $R^{(1)}$ provided by d_1 .

317

318

3	c_1	c_2	c_3	c_4
x_1	s_2	s_1	s_2	s_8
x_2	s_7	s_8	s_6	s_8
x_3	s_5	s_6	s_4	s_4
x_4	s_6	s_8	s_5	s_7

319 **Table 2.** Decision matrix $R^{(2)}$ provided by d_2 .

320

321

322

323

324

325 **Table 3.** Decision matrix $R^{(3)}$ provided by d_3 .

4	c_1	c_2	c_3	c_4
x_1	$(s_4, 0)$	$(s_4, 0)$	$(s_1, 0)$	$(s_5, 0)$
x_2	$(s_3, 0)$	$(s_6, 0)$	$(s_5, 0)$	$(s_8, 0)$
x_3	$(s_3, 0)$	$(s_2, 0)$	$(s_7, 0)$	$(s_5, 0)$
x_4	$(s_8, 0)$	$(s_1, 0)$	$(s_3, 0)$	$(s_6, 0)$

326
327 **Step 1.**
328 Transform the
329 linguistic
330 decision
331 matrix
332
333
334

335 s $R^{(k)} = (r_{ij}^{(k)})_{4 \times 4}$ ($k = 1, 2, 3$) given in Tables 1-3 into 2-tuple linguistic decision matrices

1	c_1	c_2	c_3	c_4
x_1	s_4	s_4	s_1	s_5
x_2	s_3	s_6	s_5	s_8
x_3	s_3	s_2	s_7	s_5
x_4	s_8	s_1	s_3	s_6

336 $\bar{R}^{(k)} = ((r_{ij}^{(k)}, 0))_{4 \times 4}$ ($k = 1, 2, 3$) which are given in Tables 4-6.

337 **Table 4.** 2-tuple linguistic decision matrix $\bar{R}^{(1)}$.

338

2	c_1	c_2	c_3	c_4
x_1	s_5	s_2	s_7	s_3
x_2	s_7	s_4	s_8	s_8
x_3	s_7	s_8	s_6	s_6
x_4	s_8	s_6	s_5	s_2

339

340

341

342

343

344
345
346
347
348
349
350
351

352 **Table 6.** 2-tuple linguistic decision matrix $\bar{R}^{(3)}$.

353
354

355 **Step 2.** Utilize Eqs. (14) and (15) to calculate the matrices $T^{(1)}$, $T^{(2)}$, and $T^{(3)}$ as follows:

356
$$T^{(1)} = \begin{pmatrix} 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 \end{pmatrix}, \quad T^{(2)} = \begin{pmatrix} 0.5000 & 0.5000 & 0.1250 & 0.6250 \\ 0.3750 & 0.7500 & 0.6250 & 1.0000 \\ 0.3750 & 0.2500 & 0.8750 & 0.6250 \\ 1.0000 & 0.1250 & 0.3750 & 0.7500 \end{pmatrix},$$

357
$$T^{(3)} = \begin{pmatrix} 0.3125 & 0.1250 & 0.1094 & 0.2344 \\ 0.3281 & 0.3750 & 0.6250 & 1.0000 \\ 0.3281 & 0.2500 & 0.6563 & 0.4688 \\ 1.0000 & 0.0938 & 0.2344 & 0.1875 \end{pmatrix}.$$

358 **Step 3.** Utilize the 2TPWA operator (Eq. (16)) to aggregate all the individual 2-tuple linguistic
359 decision matrices $\bar{R}^{(k)} = ((r_{ij}^{(k)}, 0))_{4 \times 4}$ ($k = 1, 2, 3$) into the collective 2-tuple linguistic decision

360 matrix $\bar{R} = (\bar{r}_{ij})_{4 \times 4} = ((r_{ij}, \alpha_{ij}))_{4 \times 4}$ (see Table 7).

Table 5. 2-tuple linguistic decision matrix $\bar{R}^{(2)}$. **Table 7.** The collective 2-tuple linguistic decision matrix $\bar{R}$.

5	c_1	c_2	c_3	c_4
x_1	$(s_5, 0)$	$(s_2, 0)$	$(s_7, 0)$	$(s_3, 0)$
x_2	$(s_7, 0)$	$(s_4, 0)$	$(s_8, 0)$	$(s_8, 0)$
x_3	$(s_7, 0)$	$(s_8, 0)$	$(s_6, 0)$	$(s_6, 0)$
x_4	$(s_8, 0)$	$(s_6, 0)$	$(s_5, 0)$	$(s_2, 0)$

363

6	c_1	c_2	c_3	c_4
x_1	$(s_2, 0)$	$(s_1, 0)$	$(s_2, 0)$	$(s_8, 0)$
x_2	$(s_7, 0)$	$(s_8, 0)$	$(s_6, 0)$	$(s_8, 0)$
x_3	$(s_5, 0)$	$(s_6, 0)$	$(s_4, 0)$	$(s_4, 0)$
x_4	$(s_6, 0)$	$(s_8, 0)$	$(s_5, 0)$	$(s_7, 0)$

364 **Step 4.** Calculate the matrix $T = (T_{ij})_{4 \times 4}$ based on Eqs. (18) and (19):

8	c_1	c_2	c_3	c_4
x_1	$(s_4, -0.2252)$	$(s_3, -0.0952)$	$(s_1, 0.2950)$	$(s_4, 0.4682)$
x_2	$(s_4, 0.2564)$	$(s_5, 0.4708)$	$(s_6, -0.0067)$	$(s_8, -0.0000)$
x_3	$(s_4, -0.0108)$	$(s_3, 0.0262)$	$(s_6, -0.2595)$	$(s_5, 0.0224)$

365
$$T = \begin{pmatrix} 1 & 0.4914 & 0.1937 & 0.0411 \\ 1 & 0.5814 & 0.4104 & 0.3135 \\ 1 & 0.5333 & 0.2444 & 0.1795 \\ 1 & 0.9167 & 0.2350 & 0.1104 \end{pmatrix}.$$

366 **Step 5.** Utilize the 2TPWA operator (Eq. (20)) to derive the collective overall preference

7	c_1	c_2	c_3	c_4
x_1	$(s_4, -0.0690)$	$(s_3, 0.1538)$	$(s_2, -0.3038)$	$(s_5, -0.2941)$
x_2	$(s_5, -0.3486)$	$(s_6, -0.3529)$	$(s_6, 0.1111)$	$(s_8, 0)$
x_3	$(s_4, 0.2661)$	$(s_4, -0.3333)$	$(s_6, -0.1235)$	$(s_5, 0.0746)$
x_4	$(s_7, 0.3333)$	$(s_2, 0.0513)$	$(s_4, -0.2427)$	$(s_5, -0.4516)$

367 value $\bar{r}_i = (r_i, \alpha_i)$ of the alternative x_i .

368 $\bar{r}_1 = (s_3, 0.4774), \bar{r}_2 = (s_6, -0.3822), \bar{r}_3 = (s_4, 0.3780), \bar{r}_4 = (s_5, -0.3146).$

369 **Step 6.** Rank the collective overall preference values $\bar{r}_i = (r_i, \alpha_i)$ ($i = 1, 2, 3, 4$) in descending
370 order.

371 $\bar{r}_2 > \bar{r}_4 > \bar{r}_3 > \bar{r}_1.$

372 Because $\bar{r}_2 > \bar{r}_4 > \bar{r}_3 > \bar{r}_1$, we have $x_2 \succ x_4 \succ x_3 \succ x_1$. Therefore, the best candidate is x_2 .

373 If we deal with Example 3.1 using the 2TPWG operator instead of the 2TPWA operator, then
374 the main steps are shown as follows:

375 **Step 1'**: See Step 1.

376 **Step 2'**: See Step 2.

377 **Step 3'**. Utilize the 2TPWG operator (Eq. (17)) to aggregate all the individual 2-tuple
378 linguistic decision matrices $\bar{R}^{(k)} = ((r_{ij}^{(k)}, 0))_{4 \times 4}$ ($k = 1, 2, 3$) into the collective 2-tuple linguistic

379 decision matrix $\bar{R}' = (\bar{r}'_{ij})_{4 \times 4} = ((r'_{ij}, \alpha'_{ij}))_{4 \times 4}$ (see Table 8).

380

381

382 **Table 8.** The collective 2-tuple linguistic decision matrix $\bar{R}'$.

383

x_4	$(s_7, 0.2685)$	$(s_1, 0.4102)$	$(s_4, -0.3598)$	$(s_4, -0.0195)$
-------	-----------------	-----------------	------------------	------------------

384

385 **Step 4'.** Calculate the matrix $T' = (T'_{ij})_{4 \times 4}$ based on Eqs. (18) and (19):

386
$$T' = \begin{pmatrix} 1 & 0.4718 & 0.1713 & 0.0277 \\ 1 & 0.5320 & 0.3638 & 0.2726 \\ 1 & 0.4986 & 0.1886 & 0.1353 \\ 1 & 0.9086 & 0.1602 & 0.0729 \end{pmatrix}.$$

387 **Step 5'.** Utilize the 2TPWG operator (Eq. (21)) to derive the collective overall preference
388 value $\bar{r}'_i = (r'_i, \alpha'_i)$ of the alternative x_i .

389 $\bar{r}'_1 = (s_3, 0.1502), \bar{r}'_2 = (s_5, 0.1900), \bar{r}'_3 = (s_4, -0.0930), \bar{r}'_4 = (s_3, 0.3725).$

390 **Step 6'.** Rank the collective overall preference values $\bar{r}'_i = (r'_i, \alpha'_i)$ ($i = 1, 2, 3, 4$) in descending
391 order.

392 $\bar{r}'_2 > \bar{r}'_3 > \bar{r}'_4 > \bar{r}'_1.$

393 Because $\bar{r}'_2 > \bar{r}'_3 > \bar{r}'_4 > \bar{r}'_1$, we have $x_2 \succ x_3 \succ x_4 \succ x_1$. Therefore, the best candidate is x_2 .

394 Through Example 4.1, we can see that there are different priority levels among four
395 attributes and three decision makers respectively. For instance, if a candidate owns bad
396 morality, then this candidate is impossible to be selected by three decision makers, no
397 matter how well he/she performs on the other three attributes. If a candidate receives a bad
398 evaluation from university president, then he/she is also impossible to be selected no matter
399 how high evaluations he has received from the other two decision makers. Clearly, the
400 existing 2-tuple linguistic aggregation operators are difficult to deal with such cases due to
401 the fact that these operators are usually used to solve MAGDM where the attributes and the
402 decision makers are at the same priority level. However, the proposed operators in this
403 paper not only accommodate the linguistic preference information but also take the
404 prioritization among the attributes and the decision makers into account; thus, our operators
405 and approaches can effectively cope with the situations in which the attributes and the
406 decision makers are at different priority levels.

407 Recently, Zhou et al. [50] developed some uncertain linguistic prioritized aggregation
408 operators and their application to multiple attribute group decision making. Peng et al.
409 [51] developed several multigranular uncertain linguistic prioritized aggregation
410 operators and their application to multiple criteria group decision making. The main
411 differences between these two papers and our paper is that these two papers deal with
412 MAGDM problems with uncertain linguistic information, while our paper deal with
413 MAGDM problems with 2-tuple linguistic information. As shown in the introduction
414 section, uncertain linguistic model computes with words directly, while the 2-tuple linguistic
415 computational model uses the 2-tuple linguistic representation and computational model to
416 make linguistic computations, which is more reasonable and reliable than uncertain linguistic
417 model in some practical situations [12-15]. As a consequence, the developed 2-tuple
418 prioritized aggregation operators are more reasonable and effective than uncertain linguistic
419 prioritized aggregation operators and multigranular uncertain linguistic prioritized
420 aggregation operators in some practical MAGDM problems.

421

422 5. CONCLUSIONS

423

424 Considering that there may exist a prioritization relationship over the attributes and decision
425 makers in some multiple attribute group decision making problems with linguistic information,
426 this paper provides some 2-tuple prioritized aggregation operators to handle the multiple
427 attribute group decision making problems where there exists a prioritization relationship over

the attributes and decision makers. The significant feature of these operators is that they not only deal with the linguistic and interval linguistic information but also take the prioritization relationship among the arguments into account. Furthermore, we apply the proposed operators to solve some multiple attribute group decision making problems and propose an approach to multiple attribute group decision making under linguistic environment in which the attributes and decision makers are in different priority level. Finally, some illustrative examples are employed to show that the proposed approaches are not only more reasonable but more efficient in practical applications due to the fact that these approaches consider the prioritization relationship among the attributes and decision makers. The limitation of this paper is that we only propose the 2TPWA operator and the 2TPWG operator and do not propose the ordered weighted forms of them, such as the 2TPOWA and 2TPOWG operators and the hybrid forms. In the future, we will focus on addressing this issue and extending the prioritized aggregation (PA) operators to the other domains.

ACKNOWLEDGEMENTS

The authors thank the anonymous referees for their valuable suggestions in improving this paper. This work is supported by the National Natural Science Foundation of China (Grant Nos. 61073121, 71271070, and 61375075) and the Natural Science Foundation of Hebei Province of China (Grant Nos. F2012201020 and A2012201033).

COMPETING INTERESTS

AUTHORS' CONTRIBUTIONS

'Zhiming Zhang' designed the study, performed the statistical analysis, wrote the protocol, and wrote the overall draft of the manuscript. The author read and approved the final manuscript.

REFERENCES

- [1] P.P. Bonissone, K.S. Decker, Selecting uncertainty calculi and granularity: an experiment in trading-off precision and complexity, in: L.H. Kanal, J.F. Lemmer (Eds.), *Uncertainty in Artificial Intelligence*, North-Holland, Amsterdam, 1986, pp. 217-247.
- [2] S. Cebi, C. Kahraman, Developing a group decision support system based on fuzzy information axiom, *Knowledge-Based Systems* 23 (2010) 3-16.
- [3] C.T. Chen, W.S. Tai, Measuring the intellectual capital performance based on 2-tuple fuzzy linguistic information, in: *Proceedings of the 10th Annual Meeting of Asia Pacific Region of Decision Sciences Institute*, Taiwan, 2005.
- [4] S.M. Chen, J.M. Tan, Handling multicriteria fuzzy decision-making problems based on vague set theory, *Fuzzy Sets and Systems* 67 (1994) 163-172.
- [5] R. Degani, G. Bortolan, The problem of linguistic approximation in clinical decision making, *International Journal of Approximate Reasoning* 2 (1988) 143-162.
- [6] M. Delgado, F. Herrera, E. Herrera-Viedma, M.J. Martin-Bautista, L. Martinez, M.A. Vila, A communication model based on the 2-tuple fuzzy linguistic representation for a distributed intelligent agent system on internet, *Soft Computing* 6 (2002) 320-328.
- [7] M. Delgado, J. L. Verdegay, M. A. Vila, On aggregation operations of linguistic labels, *International Journal of Intelligent Systems* 8 (1993) 351-370.
- [8] Y.C. Dong, Y.F. Xu, H.Y. Li, B. Feng, The OWA-based consensus operator under linguistic representation models using position indexes, *European Journal of Operational Research* 203 (2010) 455-463.

- 479 [9] C.Y. Gao, D.H. Peng, SWOT analysis with nonhomogeneous uncertain preference
480 information, *Knowledge-Based Systems* 24 (2011) 796-808.
- 481 [10] F. Herrera, E. Herrera-Viedma, Linguistic decision analysis: steps for solving decision
482 problems under linguistic information, *Fuzzy Sets and Systems* 115 (2000) 67-82.
- 483 [11] F. Herrera, E. Herrera-Viedma, L. Martínez, A fusion approach for managing multi-
484 granularity linguistic terms sets in decision making, *Fuzzy Sets and Systems* 114 (2000)
485 43-58.
- 486 [12] F. Herrera, L. Martínez, A 2-tuple fuzzy linguistic representation model for computing
487 with words, *IEEE Transactions on Fuzzy Systems* 8 (2000) 746-752.
- 488 [13] F. Herrera, L. Martínez, An approach for combining linguistic and numerical information
489 based on 2-tuple fuzzy linguistic representation model in decision-making, *International*
490 *Journal of Uncertainty, Fuzziness, Knowledge-Based Systems* 8 (2000) 539-562.
- 491 [14] F. Herrera, L. Martínez, A model based on linguistic 2-tuples for dealing with
492 multigranular hierarchical linguistic contexts in multi-expert decision making, *IEEE*
493 *Transactions on Systems, Man, and Cybernetics-Part B: Cybernetics* 31 (2001) 227-234.
- 494 [15] F. Herrera, L. Martínez, P.J. Sanchez, Managing non-homogeneous information in
495 group decision-making, *European Journal of Operational Research* 166 (2005) 115-132.
- 496 [16] E. Herrera-Viedma, S. Alonso, F. Herrera, F. Chiclana, A consensus model for group
497 decision making with incomplete fuzzy preference relations, *IEEE Transactions on*
498 *Fuzzy Systems* 15 (5) (2007) 863-877.
- 499 [17] D.H. Hong, C.H. Choi, Multicriteria fuzzy decision-making problems based on vague set
500 theory, *Fuzzy Sets and Systems* 114 (2000) 103-113.
- 501 [18] Y. P. Jiang, Z. P. Fan, Property analysis of the aggregation operators for 2-tuple
502 linguistic information, *Control and Decision*, 18(6) (2003) 754-757 (in Chinese).
- 503 [19] M. Noor-E-Alam, T.F. Lipi, M.A.A. Hasin, A.M.M.S. Ullah, Algorithms for fuzzy multi
504 expert multi criteria decision making (ME-MCDM), *Knowledge-Based Systems* 24
505 (2011) 367-377.
- 506 [20] V. Torra, Y. Narukawa, *Modeling Decisions: Information Fusion and Aggregation*
507 *Operators*, Springer, 2007.
- 508 [21] G. W. Wei, A method for multiple attribute group decision making based on the ET-WG
509 and ET-OWG operators with 2-tuple linguistic information, *Expert Systems with*
510 *Applications* 37(12) (2010) 7895-7900.
- 511 [22] G. W. Wei, Some generalized aggregating operators with linguistic information and their
512 application to multiple attribute group decision making, *Computers & Industrial*
513 *Engineering* 61 (2011) 32-38.
- 514 [23] G. W. Wei, Hesitant fuzzy prioritized operators and their application to multiple attribute
515 decision making, *Knowledge-Based Systems* 31 (2012) 176-182.
- 516 [24] Z.B. Wu, Y.H. Chen, The maximizing deviation method for group multiple attribute
517 decision making under linguistic environment, *Fuzzy Sets and Systems* 158 (2007)
518 1608-1617.
- 519 [25] Z.S. Xu, On consistency of the weighted geometric mean complex judgment matrix in
520 AHP, *European Journal of Operational Research* 126 (2000) 683-687.
- 521 [26] Z.S. Xu, A method based on linguistic aggregation operators for group decision making
522 with linguistic preference relations, *Information Sciences* 166 (2004) 19-30.
- 523 [27] Z.S. Xu, EOWA and EOWG operators for aggregating linguistic labels based on
524 linguistic preference relations, *International Journal of Uncertainty, Fuzziness and*
525 *Knowledge-Based Systems* 12 (2004) 791-810.
- 526 [28] Z.S. Xu, Deviation measures of linguistic preference relations in group decision making,
527 *Omega* 33 (2005) 249-254.
- 528 [29] Z.S. Xu, On generalized induced linguistic aggregation operators, *International Journal*
529 *of General Systems* 35 (2006) 17-28.
- 530 [30] Z.S. Xu, Induced uncertain linguistic OWA operators applied to group decision making,
531 *Information Fusion* 7 (2006) 231-238.

- [31] Z.S. Xu, An approach based on the uncertain LOWG and induced uncertain LOWG operators to group decision making with uncertain multiplicative linguistic preference relations, *Decision Support Systems* 41 (2006) 488-499.
- [32] Y.J. Xu, Z.J. Cai, Standard deviation method for determining the weights of group multiple attribute decision making under uncertain linguistic environment, in: *The 7th World Congress on Intelligent Control and Automation*, IEEE, Chongqing, China, 2008, pp. 8311-8316.
- [33] Y.J. Xu, Q.L. Da, Standard and mean deviation methods for linguistic group decision making and their applications, *Expert Systems with Applications* 37 (2010) 5905-5912.
- [34] Y.J. Xu, L. Huang, An approach to group decision making problems based on 2-tuple linguistic aggregation operators, in: *ISECS International Colloquium on Computing, Communication, Control, and Management*, IEEE Computer Society, Guangzhou, China, 2008, pp. 73-77.
- [35] Y. J. Xu, J. M. Merigó, H. M. Wang, Linguistic power aggregation operators and their application to multiple attribute group decision making, *Applied Mathematical Modelling* (2012), doi:10.1016/j.apm.2011.12.002.
- [36] Y.J. Xu, H.M. Wang, Approaches based on 2-tuple linguistic power aggregation operators for multiple attribute group decision making under linguistic environment, *Applied Soft Computing* 11 (2011) 3988-3997.
- [37] R.R. Yager, Modeling prioritized multi-criteria decision making, *IEEE Transactions on Systems, Man and Cybernetics, Part B. Cybernetics* 34 (2004) 2396-2404.
- [38] R.R. Yager, Prioritized aggregation operators, *International Journal of Approximate Reasoning* 48 (2008) 263-274.
- [39] R.R. Yager, Prioritized OWA aggregation, *Fuzzy Optimization and Decision Making* 8 (2009) 245-262.
- [40] R.R. Yager, G. Giray, Z. Marek, Using a web personal evaluation tool-PET for lexicographic multi-criteria service selection, *Knowledge-Based Systems* 24 (2011) 929-942.
- [41] D. J. Yu, Y. Y. Wu, T. Lu, Interval-valued intuitionistic fuzzy prioritized operators and their application in group decision making, *Knowledge-based Systems* 30 (2012) 57-66.
- [42] X. Yu, Z. Xu, Prioritized intuitionistic fuzzy aggregation operators, *Informat. Fusion* 14(1) (2013) 108-116.
- [43] H. M. Zhang, The multi attribute group decision making method based on aggregation operators with interval-valued 2-tuple linguistic information, *Mathematical and Computer Modelling* 56(1-2) (2012) 27-35.
- [44] Liao HC, Xu ZS. Some new hybrid weighted aggregation operators under hesitant fuzzy multi-criteria decision making environment. *Journal of Intelligent & Fuzzy Systems*, 2014;26(4):1601-1607.
- [45] Liao HC, Xu ZS, Xia MM. Multiplicative consistency of hesitant fuzzy preference relation and its application in group decision making. *International Journal of Information Technology & Decision Making*, 2014;13(1):47-76.
- [46] Liao HC, Xu ZS, Zeng XJ. Distance and similarity measures for hesitant fuzzy linguistic term sets and their application in multi-criteria decision making. *Information Sciences*, 2014;271:125-142.
- [47] Liao HC, Xu ZS. Automatic procedures for group decision making with intuitionistic fuzzy preference relations. *Journal of Intelligent & Fuzzy Systems*, (2014) DOI:10.3233/IFS-141203.
- [48] Xu ZS, Liao HC. Intuitionistic Fuzzy Analytic Hierarchy Process. *IEEE Transactions on Fuzzy Systems*, (2014) doi: 10.1109/TFUZZ.2013.2272585.
- [49] Liao HC, Xu ZS. Priorities of intuitionistic fuzzy preference relation based on multiplicative consistency. *IEEE Transactions on Fuzzy Systems*, (2014) doi: 10.1109/TFUZZ.2014.2302495.

- 584 [50] L.Y. Zhou, R. Lin, X.F. Zhao, G.W. Wei. Uncertain linguistic prioritized aggregation
585 operators and their application to multiple attribute group decision making. International
586 Journal of Uncertainty, Fuzziness and Knowledge-Based Systems, 2013, 21(4).
587 [51] D.H. Peng, T.D. Wang, C.Y. Gao, H. Wang. Multigranular uncertain linguistic prioritized
588 aggregation operators and their application to multiple criteria group decision making.
589 Journal of Applied Mathematics, Volume 2013 (2013), Article ID 857916, 13 pages.