

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17

4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17

17

18  
19  
20  
21  
22  
23  
24  
25  
26

The most dangerous toxic elements listed by the European Economic Community on a “Black List”, were Hg and Cd, while the less dangerous substances forming the “Grey List” were Zinc, Copper, Nickel, Chromium, Lead, Selenium, Arsenic, Antimony, Molybdenum and Titanium [1]. Cadmium is present in wastewaters from metallurgical alloying, ceramics, electroplating, photography, pigment works, textile printing, chemical industries and lead mine drainage. The application of phosphate fertilizers or sewage sludge may increase cadmium levels in soil, which can cause increases in cadmium levels in crops [2]. The average cadmium content of sea water is about 0.1 µg/l or less [4]. While river water contains dissolved cadmium at concentration of < 1.1 - 13.5 ng/l, Cadmium levels of up to 5 mg/kg have been reported in river and lake sediments and from 0.03 to 1 mg/kg in marine sediments [5]. A drinking water guideline value of

0.003 mg/l has been set for cadmium by WHO. In addition, the provisional tolerable weekly cadmium intake must not exceed 7 µg/kg of body weight [6]. The guideline value for lead in drinking water given by WHO is 0.01 mg/l [6].

The present study aimed to achieve an efficient non-expensive and environmentally safe method to decontaminate heavy metals (Pb and Cd) from polluted wastewater. Natural and non expensive materials, shale, alginite, and iron oxide, were used to decontaminate heavy metals polluted water to be suitable for discharging in drains and sanitary sewer system. At the end of remediation trials, the remedy agents can be removed easily, then recycled and utilized in manufacturing of building materials.

## **Material and methods**

### ***Synthesized polluted water***

Synthesized polluted water were prepared by accurate dilution of standard heavy metals solution of 1000 mg/l to known concentrations using distilled water. Lead polluted water was prepared using lead stock solution (1000 mg Pb/l in 0.5 M HNO<sub>3</sub> as matrix). A series of standard lead solutions of 5, 10, 50 and 100 mg Pb/l were prepared and used to test the ability of remedy agents in Pb removal. Cadmium polluted water was prepared using cadmium stock solution (1000 mg Cd/l in 0.5 M HNO<sub>3</sub> as matrix). A series of standard cadmium solutions of 5, 10, 20 and 50 mg Cd/l were prepared and used to test the efficiency of remedy agents in Cd removal.

### ***Remedy Agents***

Three remedy agents, alginite, shale, and iron oxide, were used for polluted water remediation trials. These agents are common, inexpensive and easy to obtain. Besides, they could be separated easily from treated water at the end of the remediation process. These agents were selected based on their negatively charged surface and high adsorption capacity, which was attributed to their high surface area. The important Characteristics of the remedy agents are summarized in the following paragraphs.

**Alginite:** Alginite is a natural rock out of the oil shale family. It originated from fossil algae biomass and pumice, descends from the mine in Gerce, Hungary. The essential ingredients of alginite [14] are high of organic matter (19%), clay (54%) and lime content (22%). The clay is rich in montmorillonite (52%).

**Shale:** Shale is a naturally occurring material exists in many places in Egypt at different depths. It mainly consists of clay (55%). The clay is rich in Montmorillonite. Chemical analysis showed that the shale

contains high amount of salt, the electrical conductivity (EC) of 1:2.5 water extract equals 10.63 dS/m and pH = 7.31. Sodium was the dominate cation.

**Iron Oxide (60 % Fe):** The sample of iron oxide is imported from Roseland Kazreti. The Chemical composition of the iron Oxide is Fe<sub>d</sub> (60%), Fe<sub>o</sub> (19%), Al (0.16 mg/ kg), Zn (12.8 mg/kg) and Cu (9.94mg/kg).

## Remediation studies

Remedy agents of Alginit, shale, and iron oxide, were added to heavy metals polluted water at different solid: solution ratios of 1:10000, 1:1000 and 1:100. The mixtures were then gently agitated and subjected to different equilibrium periods of 1, 5 and 24 hrs. At the end of each equilibrium period, the supernatant solution was obtained by centrifuging the mixtures at 3000 rpm for 10 minutes. Concentrations of studied heavy metals (Pb and Cd) were measured before adding the remedy agent and at the end of equilibrium period as well as the pH and electrical Conductivity (Ec). All trials were done in three replicates.

## Analytical procedures

Total concentrations of heavy metals (Pb, Cd, Ni, Co, Zn, Mn, Cu and Cr) were determined in both suspended matter and clear water. Suspended matter was digested using Aqua Regia method [15]. Concentrations of Pb and Cd in polluted water as well as treated ones were determined using Atomic Absorption Spectrophotometer (UNICAM, 969) (APHA, 1998). The pH was measured using digital Orion pH meter (model 420A).

The electrical conductivity (EC) of the reacted solutions was measured using digital YSIEC meter (model 35). Cation exchange capacity (CEC) of remedy agents were determined using ammonium acetate method as described by [16]. Specific surface area of remedy agents were determined using O- phenanthroline method [17].

## Statistical analyses

All statistical analyses were carried out by SAS version 9 software for all data of remediation trials. R-Squared values (R<sup>2</sup>) and Equation were considered significant (*p*-values <0.05) for the analysis of variance test (ANOVA).

## Results and discussion

84 Efficiency of remedy agents (shale, alginite and iron oxides) to remove Pb and Cd from synthetically  
85 polluted water containing various concentrations of 5, 10 and 50 mg/l were examined using different  
86 addition ratios (1:10000, 1:1000 and 1:100) of remedy agents: polluted water, at different reaction periods  
87 varying between 1 to 24 hour. The results obtained are as the follows.

## 88 *Shale*

89 The results (Table 1) showed that, although at the low addition ratio (shale: heavy metal polluted water) of  
90 1: 10000 had no pronounced ability to remove Pb from polluted water, it was effective in removing Cd  
91 from solutions containing low concentration of 5 mg/l. Shale reduced the initial concentration from 5 to  
92 0.55 mg Cd/l in a reaction period of one hour. As the addition ratio increased to 1:1000, the removal  
93 efficiency increased, particularly for Pb. Shale was able to reduce the initial concentration of Pb and Cd  
94 from 5 to 1.14 and 0.34 mg/l, respectively, in one hour reaction time. As the addition ratio increased to 1:  
95 100, the efficiency greatly increased. Shale successfully reduced the initial Pb concentration of 5 and 10 to  
96 0.4 and 0.7 mg/l, in a reaction period of 1 hour which were lower than the permissible level (5 mg/l) for  
97 irrigation water [18]. The corresponding values for Cd were 0.22 and 0.74 mg/l. Although these values are  
98 much lower than the initial one, they were higher than the permissible level (0.01mg/l) for irrigation water.  
99 Shale proved efficient in the remediation of higher concentration of 20 mg Cd /l at high addition ratio of  
100 1:100. It reduces Cd concentration from 20 to 1.5 mg /l in a matter of 2 hour reaction time. Shale has  
101 negligible ability to remove Pb and Cd from solutions containing high concentrations of 50 mg/l of Pb and  
102 Cd. In general, the obtained results showed that shale has higher efficiency to remove Cd rather than Pb.  
103 This efficiency could be attributed to high CEC values of shale (Table 2) and at the same time to the  
104 character of Cd which is attracted to the negatively charged sites and exist in diffuse ion swarm as  
105 exchangeable cation rather than forming inner sphere complex with surface functional groups which is a  
106 characteristic of Pb.

107 **Table 1. Concentrations of Pb and Cd in polluted water before and after treating with shale at addition ratios of 1:10000, 1:1000 and 1:100 for different reaction times.**

108

109

110

111

Addition ratio	Heavy metal	5(mg/l)			R <sup>2</sup>	10(mg/l)			R <sup>2</sup>	50(mg/l)			R <sup>2</sup>	LSD(5%) for 24h
		1(h)	5(h)	24(h)		1(h)	5(h)	24(h)		1(h)	5(h)	24(h)		
1:10000	<b>Pb</b>	4.11	4.20	4.18	<b>0.8450</b>	8.10	7.70	9.24	<b>0.8364</b>	40.30	38.70	45.04	<b>0.8422</b>	<b>0.26</b>
1:10000	<b>Cd</b>	0.55	3.80	3.40	<b>0.8465</b>	8.80	5.40	9.20	<b>0.9408</b>	46.50	33.00	52.36	<b>0.9202</b>	<b>0.22</b>
1:1000	<b>Pb</b>	1.14	1.14	1.68	<b>0.9735</b>	2.70	2.60	4.40	<b>0.9553</b>	32.70	32.70	39.77	<b>0.9735</b>	<b>0.30</b>
1:1000	<b>Cd</b>	0.34	1.11	1.43	<b>0.8793</b>	5.00	3.00	4.40	<b>0.9113</b>	41.50	28.80	50.00	<b>0.911</b>	<b>0.26</b>
1:100	<b>Pb</b>	0.40	0.40	0.20	<b>0.9735</b>	0.70	0.51	0.98	<b>0.9640</b>	14.50	15.30	21.59	<b>0.9964</b>	<b>0.32</b>
1:100	<b>Cd</b>	0.22	0.21	0.07	<b>0.9893</b>	0.74	0.77	0.68	<b>0.8607</b>	17.80	13.60	14.00	<b>0.9976</b>	<b>0.31</b>

112

113

114

115

116 Table 2. Cation exchange capacity (CEC) and surface area of remedy agents.

Remedy Agent	CEC {Cmol <sub>(c)</sub> /kg}	Surface area (m <sup>2</sup> /g)
Shale	60.13	165
Alginit	34.99	81
Iron oxide	7.49	150

117

118

119

120

121 The results (Table 1) showed that the efficiency of shale in removing Pb and Cd from polluted  
 122 water was higher at shorter equilibrium period of one hour rather than longer ones which could be  
 123 attributed to the release of exchangeable cations initially existing in the interlayer of clay minerals, then  
 124 replacing Pb and Cd readily exchanged to the surface. So that, higher reaction time of 24 h is not  
 125 recommended for shale. Similar trails have been done [20] using alkali-treated oil shale ash as adsorbent to  
 126 remove lead and cadmium ions from aqueous solutions. They reported that adsorption of lead and cadmium  
 127 ions by the modified oil shale ash depended on adsorbent concentration, ash particle size, contact time and  
 128 pH of solution. At initial concentration of an aqueous solution of 10mg/L and that of the adsorbent 5g/L,  
 129 91% of lead and cadmium ions was removed from the solution. These results proved lower efficiency of  
 130 the modified oil shale ash compared with the shale sample utilized in our research

131 *Alginit*

132 The lowest addition ratio of 1:10000 was not effective even for low concentration of 5 mg Pb/l. The higher  
 133 addition ratio of 1:1000 (Table 3) was effective only for relatively low concentration of 5mg /l, which is  
 134 considerably reduced to 0.52 mg/l in a reaction time of 24 h. The efficiency of alginit in remediation of Pb  
 135 polluted water increased as the addition ratio increased. Addition ratio of 1:100 significantly eliminates Pb

136 from polluted water containing 5 and 10 mg Pb/l in a reaction time of 24h, Pb concentration in the previous  
137 solutions reduced to 0.21 and 0.46 mg/l, respectively. For water highly polluted with 50 mg Pb /l, addition  
138 ratio of 1:100 was able to reduce Pb to concentration (6.5 mg/l) little higher than the permissible level.

139 Regarding Cd, addition ratios of 1:10000 and 1:1000, gave low efficiency in removing Cd from polluted  
140 water. However, addition ratio of 1:100 proved more efficient in eliminating Cd from polluted water. It  
141 reduces the initial Cd concentrations of 5 and 10 to 0.21 and 1.57 mg/l, respectively. The results showed  
142 that, removal of Cd by alginite was time dependent since the changes in pollutant concentrations with time  
143 were significant ( $LSD_{0.05}$  ranged from 0.20 – 0.33). Based on Cd permissible level for irrigation water (0.01  
144 mg/l), alginite showed low efficiency in Cd removal. It works only with low Cd concentration at high  
145 addition ratio of 1:100. Based on these results, it could be concluded that, unlike shale, alginite has higher  
146 efficiency in the removal of Pb rather than Cd, which could be attributed to the relatively low CEC value  
147 (34.99  $Cmol_{(c)}/kg$ ) of alginite (Table 2) comparing with shale (60.13  $Cmol_{(c)}/kg$ ), *i.e.* low electrostatic  
148 attraction between Cd and alginite surface which led to low Cd removal via exchange process. Therefore,  
149 specific adsorption of Pb is more likely to be dominant on alginite surface than the exchange process

150

151      **Table 3. Concentrations of Pb and Cd in polluted water before and after treating with alginit at addition ratios of 1:10000, 1:1000 and 1:100 for different reaction times**

152

153

Addition ratio	Heavy metal	5(mg/l)				10(mg/l)				50(mg/l)				LSD (5%) for 24 h
		1(h)	5(h)	24(h)	R <sup>2</sup>	1(h)	5(h)	24(h)	R <sup>2</sup>	1(h)	5(h)	24(h)	R <sup>2</sup>	
1:10000	Pb	5.00	4.73	4.70	0.8733	10.00	9.50	9.50	0.8018	40.10	40.80	40.30	0.9985	0.26
1:10000	Cd	5.00	5.00	5.00	Nd	8.90	10.00	5.50	0.8483	47.40	46.50	39.60	0.9967	0.32
1:1000	Pb	1.85	1.2	0.52	0.8843	9.01	8.10	9.68	0.9117	40.20	39.70	38.50	0.9352	0.20
1:1000	Cd	2.80	4.40	3.20	0.9691	9.10	8.00	5.20	0.9872	50.00	48.90	50.00	0.9859	0.33
1:100	Pb	0.04	0.21	0.21	0.8803	0.40	0.42	0.46	0.9868	19.80	17.90	6.50	0.9990	0.31
1:100	Cd	0.29	0.23	0.21	0.2845	2.00	1.70	1.57	0.9307	47.40	39.90	30.00	0.9233	0.31



154

155

156

157 ***Iron oxide***

158 Table (4) shows the concentration of Pb and Cd in polluted water before and after treating with iron oxide  
159 at addition ratios of 1:10000, 1:1000 and 1:100 for different reaction times. At the lowest addition ratio of  
160 1:10000, iron oxide proved not efficiency to remove Pb even from water polluted with low concentrations  
161 of 5 mg/l. As the addition ratio increased to 1:1000, iron oxide worked well with low Pb concentration of 5  
162 mg /l and reduced the initial concentration to 0.67 mg/l. However, for water polluted with higher Pb  
163 concentration of 10 mg/l, the efficiency dropped, in which the initial concentration reduced to be 3.5 mg/l  
164 in a reaction time of 24 hour. Iron oxide can be potentially efficient in removing Pb from polluted water  
165 only at high addition ratio of 1:100. This efficiency increased even for high Pb concentration of 50 mg/l.  
166 Also the removal efficiency increased significantly ( $R^2=0.888$ ) as the reaction time increased. In a reaction  
167 time of 24 hour, it eliminated Pb from solutions of initial concentration of 5 and 10, with the concentrations  
168 reduced to undetectable value (Table 4). Also, it reduced the concentration of 50 mg Pb/l to 1.67 mg/l  
169 where is lower than the permissible level (5 mg/l) for irrigation water.

170 The efficiency of Fe-oxide in removing Cd was significantly ( $LSD_{0.05}=0.24-0.32$ ) time dependent. As the  
171 reaction period increased, Cd concentration in the equilibrium solution decreased. High addition ratio of  
172 1:100 was the most effective in removing Cd. At addition ratio of 1:100, iron oxide efficiently reduced the  
173 initial concentrations of 5 and 10 mg Cd/l to 0.1 and 0.4 mg/l, respectively, in a reaction period of 24 h.  
174 These concentrations (0.1 and 0.4 mg/l) were higher than the permissible level (0.01 mg/l) for irrigation  
175 water. Although, several methods have been adopted to remove heavy metals from polluted water, these  
176 methods succeeded only with water of high pH values and low concentrations of pollutants. At acidic  
177 conditions and relatively high concentrations of pollutants, the efficiency of these methods were limited.  
178 On the other hand, the techniques utilized in our research succeeded in decontaminate water of low pH  
179 values and high concentrations of Pb and Cd. Among these methods [21] stated, that waste iron  
180 (III)/chromium (III) hydroxide has been used as an adsorbent for the effective removal of Pb(II) from  
181 aqueous solution at pH greater than 7.0. The percent adsorption of Pb(II) increased with a decrease in  
182 concentration of Pb(II) and an increase in temperature. [22], suggested a process for removing lead from  
183 battery industry wastewater by neutralization with NaOH, in the presence of Fe(III) salts which the lead  
184 concentration of the treated effluent is below 0.2 mg/l. [23], proposed a procedure for purifying waters

185 polluted with metal ions [ Al(III), V(V), Ni(II), Cd(II), Co(II), Pb(II), Hg(II), Cr(II),  
186 Sn(II),Bi(II),Zn(II),and Cu(II)], by precipitation of metals as magnetic ferrite from the alkalized solution  
187 containing iron(II) was based on the precipitation of metals as magnetic ferrite. The maximal purification  
188 efficiency (99.99%) was achieved when waste water samples are treated for 3 hours at 50°C and pH 10,  
189 Fe(II)/Total metal ratio was 15.0 and different concentrations of  $\text{KMnO}_4$ .

190     **Table 4. Concentrations of Pb and Cd in polluted water before and after treating with iron oxide at addition ratios of 1:10000, 1:1000 and 1:100 for different**  
191     **reaction times.**

192

193

194

Addition ratio	Heavy metal	5(mg/l)				R <sup>2</sup>	10(mg/l)				R <sup>2</sup>	50(mg/l)				R <sup>2</sup>	LSD (5%) for 24h
		1(h)	5(h)	24(h)	1(h)		5(h)	24(h)	1(h)	5(h)		24(h)					
1:10000	Pb	2.76	5.00	5.00	0.851	10.10	10.00	10.00	0.906	42.60	10.78	44.04	0.853	0.25			
1:10000	Cd	4.50	2.60	3.00	0.984	0.30	10.40	8.00	0.850	47.10	52.80	42.00	0.926	0.25			
1:10000	Pb	2.76	2.60	0.67	0.991	9.60	8.53	3.50	1.000	42.60	39.82	44.83	0.879	0.29			
1:10000	Cd	3.70	2.00	2.00	0.842	2.10	9.20	8.80	0.796	49.80	49.20	49.40	0.962	0.24			
1:100	Pb	0.27	Nd	Nd	0.402	0.20	0.28	Nd	0.815	29.01	15.80	1.68	0.888	-			
1:100	Cd	0.70	0.34	0.10	0.790	4.00	2.40	0.40	0.915	38.80	44.00	34.00	0.880	0.32			

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

## 210 **Conclusion**

211 All remedy agents, shale, alginite and iron oxides, proved potential efficiency in the removal of Pb and Cd  
212 from water polluted of wide range of Pb and Cd varied between 5 to 50 mg/l. Generally, their efficiency  
213 increased as the addition ratio between remedy agents and polluted water increased from 1:10000 – 1:100.  
214 Among all tested agents, shale had highest efficiency for the removal of Cd. It had high potential ability to  
215 remediate higher concentration of 20 mg Cd /l at addition ratio of 1:100. However, shorter equilibrium  
216 period of 1 hour was more effective than the higher one of 24 h. Alginite proved high efficiency in removing  
217 Pb and Cd from polluted water when added at high ratio of 1:100. Unlike shale, alginite had a higher  
218 removal efficiency for Pb rather than Cd. Iron oxide had potential efficiency in removing Pb from polluted  
219 water only at high addition ratio of 1:100. This efficiency was shown even for high Pb concentration of 50

220 mg/l. In a reaction period of 24 hour, it **eliminated** Pb from solutions of initial concentration of 5 and 10,  
221 **mg/l**, while **reducing** the concentration of 50 to a level (1.67 mg/l) lower than irrigation water permissible  
222 level (5 mg/l).

223

224

## 225 REFERENCES

226 1 - Bond PBR. Aspects of the European Investment Bank's Experience in Wastewater management. The  
227 Second Middle East Conf, on Wastewater Mgt., Cairo,pp. 323-330. 1995.

228 2 -Gadd GM, White C. Microbial Treatment of Metal Pollution, A Working Biotechnology. Trends  
229 Biotechnol, 1993; 11(8): 353-359.

230 3 - Evangelou VP. Environmental Soil and Water Chemistry principles and applications. Iowa State  
231 University, Iowa, John Wiley and Sons, Inc. New York, 564p. 1998.

232 4 - Egyptian Environmental Affairs Agency EEAA. Environmental Action Plan of Egypt. Cairo, Egypt, 246p.  
233 1992.

234 5 - Eckenfelder W, Wesley JR. Industrial Water Pollution Control. 2<sup>nd</sup>, McGraw-Hill book company, ISBN:  
235 007018903X. 1989.

236 6 - World Health Organization WHO. Guidelines for drinking water quality health criteria and other  
237 supporting information." Geneva, World Health Organization, 2: 84-90; 1984.

238 7 - Wilson B, Pyatt FB. Heavy metal dispersion, persistence, and bioaccumulation around an ancient  
239 copper mine situated in Anglesey. UK. Ecotoxicology and Environmental Safety; 2007;. 66: 224-  
240 231.

241 8 - Statistics Canada. Freshwater supply and demand in Canada,"Human Activity and the Environment,  
242 Catalogue no. 16-201-X, 2010 [http://www.statcan.gc.ca/pub/16-201-x/2012000/part-partie4-](http://www.statcan.gc.ca/pub/16-201-x/2012000/part-partie4-eng.htm)  
243 [eng.htm](http://www.statcan.gc.ca/pub/16-201-x/2012000/part-partie4-eng.htm)

244 9 - Hagberg, A. Industrial wastewater treatment and other environmental problems in WuhanIs Swedish  
245 technology a solution. Department of Earth Sciences, Uppsala University, Villavägen; 16: SE-752  
246 36 Uppsala, ISSN 1401-5765; 2007.

247 10 - Muchuweti M, Birkett JW, Chinyanga E, Zvauya, R, Scrimshaw MD, Lester JN. Heavy metal content of  
248 vegetables irrigated with mixture of wastewater and sewage sludge in Zimbabwe: implications  
249 for human health. Agriculture Ecosystem and Environ. 2006; 1 (12): 41-48.

250 11 - Pacyna JM. Heavy Metal Emission from Industrial Sources in Europe. Chem. Environ. Proc. Int. Conf.,  
251 pp.129-137. 1986.

252 12 - United States Environmental Protection Agency "USEPA". Air Quality Criteria for Lead. Research  
253 Triangle Park, NC. (Report EPA600/8-83/028F). 1986.

254 13 - Kocaoba S, Akein G. Removal of chromium and cadmium from wastewaters with a strong cation  
255 exchange resin. Second International Water Technology Conference Alexandria, Egypt, 382p.  
256 1997.

257 14 - Terra Natural Resources TNR. Alginit- a brand of Terra Natural Resources GmbH Switzerland,  
258 Seestrasse 24. CH-8806 Wallerau SZ. Email. 2009.

259 15 - Cottenie A, Verloo M, Kiekens L, Velgh G, Camcrynck R. Chemical analysis of plant and soils, Lab.  
260 Anal, Agrochem., State Univ., Ghent, Belgium, 63p. 1982.

261 16 - Page AL, Miller RH, Keeney DR. Methods of Soil Analysis, Part 2—Chemical and Microbiological  
262 Properties. Second Edition, American Society of Agronomy, Inc. Soil Science Society of America,  
263 Inc. Publisher Madison, Wisconsin USA, 698p. 1989.

264 17 - Sparks DK. Methods of Soil Analysis. part 3. Chemical Methods. Soil Science Society of America, Inc.,  
265 Madison, Wisconsin, USA, 1390 p. 1998.

266 18 – FAO. Water quality for agriculture. R.S. Ayers and D.W. Westcott. Irrigation and Drainage Paper 29  
267 Rev. 1. FAO, Rome, 174 p. 1985.

268 19 – Batley GE. Approaches to the assessment of sediment quality. CSIRO Division of Coal and Energy  
269 Technology Investigation Report No. CET/IR274, 45 p. 1994.

270 20 - Zhu, Bo-Lin, Xiu, Zong-Ming, Liu, NA, Bi, Hai-Tao and Lv, Chun-Xin. Adsorption of lead and cadmium  
271 ions from aqueous Solutions by modified oil shale ash. Oil Shale, 2012; 29 (3): 268–278

- 272 21 - Namasivayam, C. and Ranganathan, K. Removal of lead (II) by adsorption onto waste iron  
273 (III)/chromium (III) hydroxide from aqueous solution and radiator manufacturing industry  
274 wastewater. Industrial Chemistry Research;1995; 34 (n): 4101-4104
- 275 22 - Macchi, G.; Pagano, M.; Santori, M. and Triavanti, G. Battery industry wastewater: lead removal and  
276 produced sludge. Water Research; 1993; 27(10): 1511-1518.
- 277 23 - Barrado, E.; Vega, M.; Pardo, R.; Ruiperez, M. and Medina, J. Application of the Taguchi experimental  
278 design to the removal of toxic metals from wastewaters by precipitation as magnetic ferrites.  
279 Analytical Letters; 1996; 29 (24): 613-63.
- 280