# SCIENCEDOMAIN international



### www.sciencedomain.org

## **SDI FINAL EVALUATION FORM 1.1**

## PART 1:

Journal Name:	Physical Science International Journal
Manuscript Number:	2014_PSIJ_12624
Title of the Manuscript:	Dry Sliding Wear Behaviour of Plasma Sprayed Fly Ash Added Red Mud Coatings

### PART 2:

FINAL EVALUATOR'S comments on revised paper (if any)	Authors' response to final evaluator's comments
I am still not convinced regarding the language-whether it is of sufficient level for a	
reader in the subject. As an ex: p1 line 8/9 says 'Plasma spraying techniques was	
involved at different levels of operating powers' It could have been 'Plasma spraying	
technique was used with varying levels of energy for the purpose of spraying'. Similarly	
line 13/14 ' mixed with red mud and allowed for the sliding wear test using pin-on-	
disc machine' I don't know what is meant by allowing for the sliding wear test'. Such	
statements are many and as a reviewer I cannot pin point each and every statement.	
Regarding mass loss in Newtons-Though explanation is given, I have not heard this	
method and the authors do not explain how it is done. Explanation is not satisfactory,	
at least from my look.	
Answer for Q5: Even if we accept the author's argument the plots do not reach a plateau	
after 12 min (400 m sliding). They reach much later. Also, I cannot understand why the	
stress is given to 6 minutes sliding? After 6 minutes the plot is in accelerating direction.	
For Q7: The presented answer does not address the question posed.	
For 8: No solution given.	
Q9: It is not correct to present a question or give future direction without basis. All of	
us can do some experiments and say more things without presenting any logic. Sorry to	
use this way.	
use uns way.	

## **Reviewer Details:**

Name:	Anonymous	
Department, University & Country	y National Institute of Technology Karnataka, Surathkal, India	